KM 652-5 small

Orange Peel Grapple

The small orange peel grapple KM 652-5 small for the handling of bulky scrap is available with five tines and three different volumes (120I, 180I, 240I).

- The KM 652-5 small is available with 5 half closing tines for handling swarf, scrap, rubbish, waste paper etc.
- Long life due to a solid design: the hydraulic cylinder pistons are protected by the gripping arms and the hydraulic hoses, connections and oil distributor are positioned in the robust centre section. Special wear resistant materials used in the production of the gripping arms and oversized bearings ensure a long service life for these sturdy grapples.
- > A lifting-eye on the centre section acts as an additional stop.
- Powerful operation with high closing force (11 kN to 13 kN at an operating pressure of 26 MPa).



Orange peel grapple KM 652-5 small									
Туре	Number of tines	Volume	Opening A	Width E	Height C	Self weight (w/o rotator)	Load capacity	Closing force	
		(litre)	(mm)	(mm)	(mm)	(kg)	(kg)	(kN)	
KM 652-5-120	5	120	1360	1065	800	300	2000	13	
KM 652-5-180	5	180	1450	1070	850	305	2000	12	
KM 652-5-240	5	240	1720	1125	985	340	2000	11	

Package consists of: orange peel grapple, non-return valve

Accessories	
Туре	Description
KM 04 F KM 04 F140-30US	recommended KINSHOFER rotator for KM 652-5 small recommended KINSHOFER rotator for KM 652-5 small – for heavy duty application
Requirements of truck crane	

Operating pressure at oil flow:

max. 26 MPa (260 bar) at 25 - max. 75 l/min Mind the pressure!

Technical drawings

