

Fork Tines for **NOX**-Tiltrotators 3-12t / 6,600-26,400lbs

GAF / GAH

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ High load capacity.
- ▷ Low self-weight.
- ▷ Very economic: low cost.
- ▷ Ideal for use with Tiltrotator: highest flexibility.
- ▷ Two versions available: with mechanically or hydraulically adjustable tines.
- ▷ Easy mounting thanks to a quick change adapter.
- ▷ Different adapters available.
- ▷ Mechanical fork tines with adapter system L-Lock, Oilquick or Verachttert without surcharge.



Mechanic Fork Tines GAF

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAF6	TR045NOX / TR07NOX	S40	1,900 / 4,180	1,000 / 39.3	140 / 308	1,000 / 39.3	3 - 6 / 6,600 - 13,200
GAF8	TR07NOX / TR11NOX	S45	1,900 / 4,180	1,200 / 47.2	190 / 418	1,000 / 39.3	6 - 8 / 13,200 - 17,600
GAF12	TR11NOX	S45	2,500 / 5,500	1,200 / 47.2	200 / 440	1,200 / 47.2	9 - 12 / 19,800 - 26,400

Package consists of: fork tines, frame with standard suspension for S-couplers*

Hydraulic Fork Tines GAH

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAH6	TR045NOX / TR07NOX	S40	1,900 / 4,180	1,000 / 39.3	160 / 352	1,000 / 39.3	3 - 6 / 6,600 - 13,200
GAH8	TR07NOX / TR11NOX	S45	1,900 / 4,180	1,200 / 47.2	210 / 462	1,000 / 39.3	6 - 8 / 13,200 - 17,600
GAH12	TR11NOX	S45	2,500 / 5,500	1,200 / 47.2	220 / 484	1,200 / 47.2	9 - 12 / 19,800 - 26,400

Package consists of: hydraulic fork tines, frame with standard suspension for S-couplers*

*other adapters available on request

Note: put loads always the nearest to the back and to the centre of gravity

Requirements for carrier machine



The excavator must be conform to lifting regulations

Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter



Hydraulically adjustable fork tines here with cylinderless **NOX** Tiltrotator

Fork Tines for **NOX**-Tiltrotators 13-24t / 28,600-52,800lbs

GAF / GAH

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF or GAH Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ High load capacity.
- ▷ Low self-weight.
- ▷ Very economic: low cost.
- ▷ Ideal for use with Tiltrotator: highest flexibility.
- ▷ Two versions available: with mechanically or hydraulically adjustable tines.
- ▷ Easy mounting thanks to a quick change adapter.
- ▷ Different adapters available.
- ▷ Mechanical fork tines with adapter system L-Lock, Oilquick or Verachtert without surcharge.



Mechanic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAF18	TR14NOX TR19NOX	S45 S60	4,000 / 8,800	1,200 / 47.2	340 / 748	1,200 / 47.2	13 - 18 / 28,600 - 39,600
GAF20	TR19NOX TR25NOX	S70	4,000 / 8,800	1,200 / 47.2	420 / 924	1,200 / 47.2	19 - 20 / 41,800 - 44,000
GAF24	TR25NOX	S70	5,000 / 11,000	1,200 / 47.2	440 / 968	1,200 / 47.2	21 - 24 / 46,200 - 52,800

Package consists of: fork tines, frame with standard suspension for S-couplers*

Hydraulic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAH18	TR14NOX TR19NOX	S45 S60	4,000 / 8,800	1,200 / 47.2	340 / 748	1,200 / 47.2	13 - 18 / 28,600 - 39,600
GAH20	TR19NOX TR25NOX	S70	4,000 / 8,800	1,200 / 47.2	420 / 924	1,200 / 47.2	19 - 20 / 41,800 - 44,000
GAH24	TR25NOX	S70	5,000 / 11,000	1,200 / 47.2	440 / 968	1,200 / 47.2	21 - 24 / 46,200 - 52,800

Package consists of: hydraulic fork tines, frame with standard suspension for S-couplers*

*other adapters available on request

Note: put loads always the nearest to the back and to the centre of gravity

Requirements for carrier machine



The excavator must be conform to lifting regulations

Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter



Hydraulically adjustable fork tines here with cylinderless NOX Tiltrotator